

CHAPTER 5

PACKAGED ROOF TOP UNITS

UNIT	Page
RTA/TK/EC/WP 182-R÷453-R	168 - 169
RTA/K/EC/WP 182-R÷453-R	170 - 171
RTA/IK/EC 172÷724	172 - 173
RTA/IK/EC/MS 172÷724	174 - 175
RTA/IK/EC/ECO 172÷724	176 - 177
RTA/IK/EC/ECO/REC-FX 172÷724	178 - 179
RTA/IK/EC/ECO/REC-WH 172÷724	180 - 181
RTA/K 182÷804	182 - 183
RTA/K/MS 182÷804	184 - 185
RTA/K/ECO 182÷804	186 - 187
RTA/K/ECO/REC-FX 182÷804	188 - 189
RTA/K/ECO/REC-WH 182÷804	190 - 191

RTA/TK/EC/WP 182-R÷453-R

SINGLE SKIN PACKAGED ROOF TOP UNITS WITH DIGITAL SCROLL COMPRESSORS AND EC INVERTER PLUG-FANS.



The single skin packaged Roof Top units of the **AIRPLUS** series are the ideal solution for air conditioning of medium-wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. The units are equipped with **Digital Scroll** compressors with R410A refrigerant, and are available in Reversible Heat Pump version also with **Free-Cooling** with 2 or 3 dampers. A better efficiency at partial loads is guaranteed by the Digital Scroll technology on compressor since its power is varied according to the requested thermal load. AIRPLUS is equipped with **EC Inverter Plug-Fans** with high energy efficiency backward blades both for intake as well as delivery, managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. The unit can easily adapt to diverse engineering needs thanks to the possibility of selecting onsite the air flow direction, choosing among 8 positions of both intake and output air direction. The unit's structure is made of a frame with extruded aluminium profiles and prepainted panels, and features flat type filters with varying efficiency levels, maintaining high air quality and high comfort.

The unit can be equipped, as an option, with the innovative **Thermodynamic Coil-Boost Heat Recovery** to achieve better performance and efficiency both in cooling and heating up to 15%.



DIGITAL SCROLL

EC INVERTER PLUG FANS

THERMODYNAMIC COIL-BOOST HEAT RECOVERY

VERSION

RTA/TK/EC/WP	RTA/TK/EC/WP/MS	RTA/TK/EC/WP/ECO
Reversible Heat Pump	Reversible Heat Pump with Free-Cooling section (2 dampers)	Reversible Heat Pump with Economizer (Free-Cooling section with 3 dampers)

FEATURES

- Structure of base perimeter made of galvanised steel sheet elements. The frame is made of extruded aluminium alloy profiles connected by 3 way joints. The assembling of the base to the frame is of dual support and grants the walking on the base panels installation of which is effected without sticking out screws. The perimeter panels are realised in prepainted sheet steel, they can be easily removed and allow access inside the unit for maintenance and repair operations.
- DIGITAL Scroll and ON-OFF Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- The air treatment section has removable panels allowing the selection of intake and output configurations that adapt to the specific needs of the system.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Electronic proportional device to decrease the sound level, with a continuous regulation of the fan speed. This device also allows the cooling functioning of the unit by external temperature till -20°C.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers	AT	Constant air flow regulation control	ISBT	BACnet TCP/IP protocol, Ethernet port
SL	Unit silencement	AT/P	Constant available static pressure regulation control	ISL	LonWorks protocol, FTT-10 serial interface
THCB	Thermodynamic Coil-Boost Heat Recovery (ECO only)	WS2	2-Row hot water coil with 3-Way valve	CP	Potential free contacts
RFM	Cooling circuit shut-off valve on discharge line	EHG	Electrical heater with step regulation		
RFL	Cooling circuit shut-off valve on liquid line	CH	Enthalpic control (ECO only)		
TXC	Condensing coil with pre-coated fins	SQ	Air quality sensor		
TXE	Evaporating coil with pre-coated fins	PF	Filter differential pressure switch		
FT	Plate filters efficiency M6-F7-F8	IS	Modbus RTU protocol, RS485 serial interface		
		ISB	BACnet MSTP protocol, RS485 serial interface		

LOOSE ACCESSORIES

MN	High and low pressure gauges
CS	Dampers rain hood
CR	Remote control panel
RP	Coil protection metallic guards
AG	Rubber shock absorbers

RTA/TK/EC/WP 182-R-453-R

MODEL			182-R	202-R	242-R	262-R	302-R	363-R	393-R	453-R
Heating	Heating capacity (1)	kW	62.9	71.1	81.2	92.9	107	123	142	162
	Absorbed power (1),(2)	kW	18.6	21.7	25.2	28.1	31.0	38.1	42.6	50.1
Heating (EN14511)	SCOP (3)		3.15	3.27	3.28	3.31	3.48	3.16	3.47	3.32
	Energy Efficiency (3)	%	123	128	128	129	136	123	136	130
Cooling	Cooling capacity (4)	kW	64.9	73.8	85.6	96.8	111	128	147	171
	Absorbed power (2),(4)	kW	20.9	24.2	27.2	30.0	35.4	41.1	45.9	54.1
Cooling (EN14511)	SEER (5)		3.43	3.38	3.44	3.48	3.38	3.44	3.55	3.52
	Energy Efficiency (5)	%	134	132	135	136	132	135	139	138
Air treatment section	Air flow	m³/s	2.50	2.78	3.34	3.61	4.44	4.44	5.83	6.67
	Available static pressure	Pa	200	200	200	200	200	200	200	200
	Fan	n°	1	1	1	1	1	1	2	2
Air intake section	Filter	Typo	G4	G4	G4	G4	G4	G4	G4	G4
	Air flow	m³/s	2.00	2.22	2.67	2.89	3.55	3.55	4.72	5.33
	Available static pressure	Pa	100	100	100	100	100	100	100	100
Condensing section	Fan	n°	1	1	1	1	1	1	1	1
	Compressor	n°	2	2	2	2	2	3	3	3
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1
Hot water coil	Capacity steps	n°	2				3			
	Heating capacity (6)	kW	65.4	68.6	74.9	78.9	84.9	84.9	103	110
	Air pressure drops	Pa	16	19	26	30	43	43	68	86
	Water flow (6)	l/s	1.56	1.64	1.79	1.89	2.03	2.03	2.46	2.62
	Water pressure drops	kPa	12	14	15	17	18	18	24	28
	Water connections	"G	2	2	2	2	2	2	2	2
Electrical heater	Power supply	V/Ph/Hz	400/3/50							
	Heating capacity	kW	21	27	27	27	40	40	40	48
	Max. absorbed current	A	30	39	39	39	59	59	59	69
	Steps	n°	2	2	2	2	4	4	4	4
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50							
	Max. running current	A	53	56	65	69	79	91	110	131
	Max. starting current	A	190	165	188	201	208	215	242	260
Sound pressure	STD/MS/ECO versions (7)	dB(A)	56	56	60	60	60	60	61	61
Weights	Transport weight	Kg	1280	1315	1370	1380	1475	1570	1920	2020
	Operating weight	Kg	1265	1300	1355	1365	1460	1555	1900	2000

MS - ECO

MS. Free-Cooling section with 2 dampers - Further to components of the basic version, includes two wing profile aluminium dampers with spring return servomotors (dampers with opposite movement).

ECO. Free-Cooling section with 3 dampers - Further to components of the basic version, includes return air EC INVERTER PLUG-FANS; motorized wing profile aluminium dampers (dampers with opposite movement). Exhaust, recirculation and fresh air are controlled through the microprocessor fitted in the base unit; this microprocessor, according to the temperature of the return and fresh air, modulates the opening of the dampers and controls the cooling circuit capacity steps to ensure comfort conditions of the handled air. The adjustments of the ECO versions are automatically controlled both in free-cooling and free-heating mode.

DIMENSIONS			182-R	202-R	242-R	262-R	302-R	363-R	393-R	453-R
L	STD/MS/ECO	mm	2930	2930	2930	2930	2930	2930	3930	3930
W	STD/MS/ECO	mm	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/MS/ECO	mm	2370	2370	2370	2370	2370	2370	2370	2370

CLEARANCE AREA

RTA/TK/EC/WP 182-R-453-R

1000 | 1800 | 1000 | 1000



NOTES

1. Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 2. Excluded the power absorbed by fans of air treatment section.
 3. Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 4. Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 5. Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 6. Inlet air temperature 20 °C, water temperature 70/60 °C.
 7. Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of MS and ECO versions are specified on technical brochure.

RTA/K/EC/WP 182-R÷453-R

SINGLE-SKIN PACKAGED ROOFTOP UNITS WITH SCROLL COMPRESSORS AND EC INVERTER PLUG-FANS.



The single skin packaged Roof Top units of the **AIRPLUS** series are the ideal solution for air conditioning of medium-wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. The units are equipped with Scroll compressors with R410A refrigerant, and are available in Reversible Heat Pump version also with **Free-Cooling** with 2 or 3 dampers. AIRPLUS is equipped with **EC Inverter Plug-Fans** with high energy efficiency backward blades both for intake as well as delivery, managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. The unit can easily adapt to diverse engineering needs thanks to the possibility of selecting onsite the air flow direction, choosing among 8 positions of both intake and output air direction. The unit's structure is made of a frame with extruded aluminium profiles and prepainted panels, and features flat type filters with varying efficiency levels, maintaining high air quality and high comfort.

The unit can be equipped, as an option, with the innovative **Thermodynamic Coil-Boost Heat Recovery** to achieve better performance and efficiency both in cooling and heating up to 15%.



EC INVERTER PLUG FANS

THERMODYNAMIC COIL-BOOST HEAT RECOVERY

VERSION

RTA/K/EC/WP

Reversible Heat Pump

RTA/K/EC/WP/MS

Reversible Heat Pump with Free-Cooling section (2 dampers)

RTA/K/EC/WP/ECO

Reversible Heat Pump with Economizer (Free-Cooling section with 3 dampers)

FEATURES

- Structure of base perimeter made of galvanised steel sheet elements. The frame is made of extruded aluminium alloy profiles connected by 3 way joints. The assembling of the base to the frame is of dual support and grants the walking on the base panels installation of which is effected without sticking out screws. The perimeter panels are realised in prepainted sheet steel, they can be easily removed and allow access inside the unit for maintenance and repair operations.
- Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- The air treatment section has removable panels allowing the selection of intake and output configurations that adapt to the specific needs of the system.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
THCB	Thermodynamic Coil-Boost Heat Recovery (ECO only)
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
CT	Condensing control down to 0 °C
CC	Condensing control down to -20 °C
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT	Plate filters efficiency M6-F7-F8
AT	Constant air flow regulation control

AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
CH	Enthalpic control (ECO only)
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts

LOOSE ACCESSORIES

MN	High and low pressure gauges
CS	Dampers rain hood
CR	Remote control panel
RP	Coil protection metallic guards
AG	Rubber shock absorbers

RTA/K/EC/WP 182-R÷453-R

MODEL			182-R	202-R	242-R	262-R	302-R	363-R	393-R	453-R
Heating	Heating capacity (1)	kW	62.9	71.1	81.2	92.9	107	123	142	162
	Absorbed power (1),(2)	kW	18.6	21.7	25.2	28.1	31.0	38.1	42.6	50.1
Heating (EN14511)	SCOP (3)		3.09	3.21	3.21	3.24	3.41	3.10	3.40	3.26
	Energy Efficiency (3)	%	121	125	125	127	133	121	133	127
Cooling	Cooling capacity (4)	kW	64.9	73.8	85.6	96.8	111	128	147	171
	Absorbed power (2),(4)	kW	20.9	24.2	27.2	30.0	35.4	41.1	45.9	54.1
Cooling (EN14511)	SEER (5)		3.18	3.16	3.28	3.38	3.32	3.31	3.41	3.39
	Energy Efficiency (5)	%	124	123	128	132	130	129	133	133
Air treatment section	Air flow	m³/s	2.50	2.78	3.34	3.61	4.44	4.44	5.83	6.67
	Available static pressure	Pa	200	200	200	200	200	200	200	200
	Fan	n°	1	1	1	1	2	2	2	2
Air intake section	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4
	Air flow	m³/s	2.00	2.22	2.67	2.89	3.55	3.55	4.72	5.33
	Available static pressure	Pa	100	100	100	100	100	100	100	100
Condensing section	Fan	n°	1	1	1	1	1	1	1	1
	Compressor	n°	2	2	2	2	2	3	3	3
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1
Hot water coil	Capacity steps	n°	2			2			3	
	Heating capacity (6)	kW	65.4	68.6	74.9	78.9	84.9	84.9	103	110
	Air pressure drops	Pa	16	19	26	30	43	43	68	86
Electrical heater	Water flow (6)	l/s	1.56	1.64	1.79	1.89	2.03	2.03	2.46	2.62
	Water connections	"G	2	2	2	2	2	2	2	2
	Power supply	V/Ph/Hz	400/3/50							
Electrical characteristics	Heating capacity	kW	21	27	27	27	40	40	40	48
	Max. absorbed current	A	30	39	39	39	59	59	59	69
	Steps	n°	2	2	2	2	4	4	4	4
Sound pressure	Power supply	V/Ph/Hz	400/3/50							
	Max. running current	A	53	56	65	69	79	91	110	131
	Max. starting current	A	190	165	188	201	208	215	242	260
Weights	STD/MS/ECO versions (7)	dB(A)	56	56	60	60	60	60	61	61
	Transport weight	Kg	1280	1315	1370	1380	1475	1570	1920	2020
Weights	Operating weight	Kg	1265	1300	1355	1365	1460	1555	1900	2000

MS - ECO

MS. Free-Cooling section with 2 dampers - Further to components of the basic version, includes two wing profile aluminium dampers with spring return servomotors (dampers with opposite movement).

ECO. Free-Cooling section with 3 dampers - Further to components of the basic version, includes return air EC INVERTER PLUG-FANS; motorized wing profile aluminium dampers (dampers with opposite movement). Exhaust, recirculation and fresh air are controlled through the microprocessor fitted in the base unit; this microprocessor, according to the temperature of the return and fresh air, modulates the opening of the dampers and controls the cooling circuit capacity steps to ensure comfort conditions of the handled air. The adjustments of the ECO versions are automatically controlled both in free-cooling and free-heating mode.

DIMENSIONS			182-R	202-R	242-R	262-R	302-R	363-R	393-R	453-R
L	STD/MS/ECO	mm	2930	2930	2930	2930	2930	2930	3930	3930
W	STD/MS/ECO	mm	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/MS/ECO	mm	2370	2370	2370	2370	2370	2370	2370	2370

CLEARANCE AREA

RTA/K/EC/WP 182-R÷453-R

1000 | 1800 | 1000 | 1000



NOTES

1. Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 2. Excluded the power absorbed by fans of air treatment section.
 3. Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 4. Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 5. Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 6. Inlet air temperature 20 °C, water temperature 70/60 °C.
 7. Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of MS and ECO versions are specified on technical brochure.

RTA/IK/EC 172÷724

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH INVERTER SCROLL COMPRESSORS AND EC INVERTER PLUG-FANS.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Inverter Scroll compressor with R410A refrigerant and **EC Inverter Plug-Fans**. The highest efficiency at partial loads is guaranteed by the Inverter Scroll technology on compressor since its power is varied proportionally to the requested thermal load. Furthermore, the EC Inverter Plug-Fans with high energy efficiency backward blades are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity.

Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.



INVERTER SCROLL

EC INVERTER PLUG FANS

VERSION

RTA/IK/EC

Cooling only with EC Inverter Plug-Fans

RTA/IK/EC/WP

Reversible Heat Pump with EC Inverter Plug-Fans

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- DC INVERTER Scroll and ON-OFF Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Electronic proportional device to decrease the sound level, with a continuous regulation of the fan speed. This device also allows the cooling functioning of the unit by external temperature till -20°C.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control
AT/P	Constant available static pressure regulation control

WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			172	192	212	232	272	302	352	372	484	574	724
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.53	3.53	3.72	3.89	3.77	3.55	3.74	3.94	3.62	3.81	3.55
	Energy Efficiency (3)	%	138	138	146	153	148	139	147	155	142	149	139
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.22	3.34	3.34	3.37	3.54	3.22	3.54	3.38	3.33	3.54	3.23
	Energy Efficiency (5)	%	126	131	131	132	139	126	139	132	130	139	126
Air treatment section	Air flow	m ³ /s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Condensing section	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
	Compressor	n°	2	2	2	2	2	2	2	2	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
	Capacity steps	n°	Stepless										
Hot water coil	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
Electrical heater	Power supply	V/Ph/Hz	400/3/50										
	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50										
	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
Sound pressure (7)		dB(A)	57	57	57	57	57	58	59	59	60	60	61
Weights	Transport weight	Kg	990	1050	1150	1250	1260	1450	1810	1860	2230	2400	3180
	Operating weight	Kg	975	1035	1135	1235	1245	1430	1790	1840	2210	2380	3150

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			172	192	212	232	272	302	352	372	484	574	724
L	STD	mm	2980	3080	3190	3190	3290	3770	4500	4500	5150	5300	7370
W	STD	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/IK/EC 172÷302



RTA/IK/EC 352÷724



NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP version are specified on technical brochure.

RTA/IK/EC/MS 172÷724

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH INVERTER SCROLL COMPRESSORS, EC INVERTER PLUG-FANS AND MIXING BOX.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Inverter Scroll compressor with R410A refrigerant and **EC Inverter Plug-Fans**. The highest efficiency at partial loads is guaranteed by the Inverter Scroll technology on compressor since its power is varied proportionally to the requested thermal load. Furthermore, the EC Inverter Plug-Fans with high energy efficiency backward blades are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity.

Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The MS units have a high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, a **MIXING BOX**.



INVERTER SCROLL

EC INVERTER PLUG FANS

VERSION

RTA/IK/EC/MS

Cooling only with EC Inverter Plug-Fans and Mixing Box

RTA/IK/EC/WP/MS

Reversible Heat Pump with EC Inverter Plug-Fans and Mixing Box

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of pre-painted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- DC INVERTER Scroll and ON-OFF Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Electronic proportional device to decrease the sound level, with a continuous regulation of the fan speed. This device also allows the cooling functioning of the unit by external temperature till -20°C.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control
AT/P	Constant available static pressure regulation control

WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			172	192	212	232	272	302	352	372	484	574	724
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.53	3.53	3.72	3.89	3.77	3.55	3.74	3.94	3.62	3.81	3.55
	Energy Efficiency (3)	%	138	138	146	153	148	139	147	155	142	149	139
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.22	3.34	3.34	3.37	3.54	3.22	3.54	3.38	3.33	3.54	3.23
	Energy Efficiency (5)	%	126	131	131	132	139	126	139	132	130	139	126
Air treatment section	Air flow	m ³ /s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Condensing section	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
	Compressor	n°	2	2	2	2	2	2	2	2	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
Hot water coil	Capacity steps	n°	Stepless										
	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
	Electrical heater	Power supply	V/Ph/Hz	400/3/50									
Heating capacity		kW	15	21	27	27	27	41	41	41	48	55	
Max. absorbed current		A	22	30	39	39	39	59	59	59	69	79	
Steps		n°	2	2	2	2	2	4	4	4	4	4	
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50										
	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
Sound pressure (7)	dB(A)	57	57	57	57	57	58	59	59	60	60	61	
Weights	Transport weight	Kg	1070	1135	1245	1340	1360	1560	1940	1990	2300	2520	3465
	Operating weight	Kg	1055	1120	1225	1320	1340	1540	1920	1970	2280	2500	3435

MIXING BOX

MS. Further to components of the basic section, includes two wing profile aluminium dampers with spring return servomotors; the opposite movement is ensured by transmission of nylon gear.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			172	192	212	232	272	302	352	372	484	574	724
L	STD	mm	3430	3530	3640	3640	3740	4220	4950	4950	5600	5750	7850
W	STD	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/IK/EC/MS 172÷302



RTA/IK/EC/MS 352÷724



Electrical board side

NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP version are specified on technical brochure.

RTA/IK/EC/ECO 172÷724

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH INVERTER SCROLL COMPRESSORS, EC INVERTER PLUG-FANS AND ECONOMIZER.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Inverter Scroll compressor with R410A refrigerant and **EC Inverter Plug-Fans**. The highest efficiency at partial loads is guaranteed by the Inverter Scroll technology on compressor since its power is varied proportionally to the requested thermal load. Furthermore, the EC Inverter Plug-Fans with high energy efficiency backward blades are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity.

Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The ECO units have a high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, an **ECONOMIZER** automatically controlled both in FREE-COOLING or FREE-HEATING.

The unit can be equipped, as an option, with the innovative **Thermodynamic Coil-Boost Heat Recovery** to achieve better performance and efficiency both in cooling and heating up to 15%.



INVERTER SCROLL

EC INVERTER PLUG FANS

THERMODYNAMIC COIL-BOOST HEAT RECOVERY

VERSION

RTA/IK/EC/ECO

Cooling only with EC Inverter Plug-Fans and Economizer

RTA/IK/EC/WP/ECO

Reversible Heat Pump with EC Inverter Plug-Fans and Economizer

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- DC INVERTER Scroll and ON-OFF Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Electronic proportional device to decrease the sound level, with a continuous regulation of the fan speed. This device also allows the cooling functioning of the unit by external temperature till -20°C.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
THCB	Thermodynamic Coil-Boost Heat Recovery (ECO only)
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8

AT	Constant air flow regulation control
AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
CH	Enthalpic control (ECO only)
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface

ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			172	192	212	232	272	302	352	372	484	574	724
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.53	3.53	3.72	3.89	3.77	3.55	3.74	3.94	3.62	3.81	3.55
	Energy Efficiency (3)	%	138	138	146	153	148	139	147	155	142	149	139
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.22	3.34	3.34	3.37	3.54	3.22	3.54	3.38	3.33	3.54	3.23
	Energy Efficiency (5)	%	126	131	131	132	139	126	139	132	130	139	126
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Air intake section	Filter	Typo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
Condensing section	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
	Compressor	n°	2	2	2	2	2	2	2	2	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
Hot water coil	Capacity steps	n°	Stepless										
	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
	Power supply	V/Ph/Hz	400/3/50										
Electrical heater	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
	Power supply	V/Ph/Hz	400/3/50										
Electrical characteristics	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
Sound pressure (7)		dB(A)	57	57	57	57	57	58	59	59	60	60	61
Weights	Transport weight	Kg	1500	1610	1740	1840	1860	2000	2400	2450	3020	3370	4190
	Operating weight	Kg	1480	1590	1720	1820	1840	1975	2375	2425	2990	3335	4150

ECONOMIZER

ECO. Further to components of the basic section, includes: return air fan with electrical motor, complete of adjustable transmission, mounted on elastic supports; motorized wing profile aluminium dampers, the opposite movement is ensured by transmission of nylon gear. Exhaust, recirculation and fresh air are controlled through the microprocessor fitted in the base unit; this microprocessor, according to the temperature of the return and fresh air, modulates the opening of the dampers and controls the cooling circuit capacity steps to ensure comfort conditions of the handled air. The adjustments of the ECO versions are automatically controlled both in free-cooling and free-heating mode.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			172	192	212	232	272	302	352	372	484	574	724
L	STD	mm	5260	5480	5570	5570	5650	6170	6900	6900	8080	8470	11020
W	STD	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/IK/EC/ECO 172-302



RTA/IK/EC/ECO 352-724



Electrical board side

NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP version are specified on technical brochure.

RTA/IK/EC/ECO/REC-FX 172÷724

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH INVERTER SCROLL COMPRESSORS, EC INVERTER PLUG-FANS, ECONOMIZER AND CROSS-FLOW HEAT RECOVERY.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Inverter Scroll compressor with R410A refrigerant and **EC Inverter Plug-Fans**. The highest efficiency at partial loads is guaranteed by the Inverter Scroll technology on compressor since its power is varied proportionally to the requested thermal load. Furthermore, the EC Inverter Plug-Fans with high energy efficiency backward blades are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity.

Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The ECO/REC-FX units have an high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, an **ECONOMIZER** automatically controlled both in FREE-COOLING or FREE-HEATING and a **CROSS-FLOW HEAT RECOVERY**.



INVERTER SCROLL

EC INVERTER PLUG FANS

VERSION

RTA/IK/EC/ECO/REC-FX

Cooling only with EC Inverter Plug-Fans, Economizer and Cross-flow Heat Recovery

RTA/IK/EC/WP/ECO/REC-FX

Reversible Heat Pump with EC Inverter Plug-Fans, Economizer and Cross-flow Heat Recovery

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- DC INVERTER Scroll and ON-OFF Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Electronic proportional device to decrease the sound level, with a continuous regulation of the fan speed. This device also allows the cooling functioning of the unit by external temperature till -20°C.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control

AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
CH	Enthalpic control (ECO only)
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface

ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			172	192	212	232	272	302	352	372	484	574	724
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.53	3.53	3.72	3.89	3.77	3.55	3.74	3.94	3.62	3.81	3.55
	Energy Efficiency (3)	%	138	138	146	153	148	139	147	155	142	149	139
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.22	3.34	3.34	3.37	3.54	3.22	3.54	3.38	3.33	3.54	3.23
	Energy Efficiency (5)	%	126	131	131	132	139	126	139	132	130	139	126
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Air intake section	Filter	Typo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
Condensing section	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
	Compressor	n°	2	2	2	2	2	2	2	2	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
	Capacity steps		Stepless										
Hot water coil	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
Electrical heater	Power supply	V/Ph/Hz	400/3/50										
	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50										
	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
Sound pressure (7)													
Weights	Transport weight	Kg	1645	1720	1910	2020	2040	2210	2640	2690	3260	3590	4390
	Operating weight	Kg	1620	1695	1885	1995	2015	2185	2610	2660	3225	3555	4350

ECONOMIZER AND CROSS-FLOW HEAT RECOVERY

ECO/REC-FX. Further to the components of the ECO section, it includes: static recovery device made of aluminium with moisture drain pan, flat filters inspectable through hinged door and dampers with return spring servomotors (fresh air damper + air recirculation damper + exhaust air damper + 2 Free-Cooling dampers). Also the adjustment of this section is included into the unit control.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			172	192	212	232	272	302	352	372	484	574	724
L	STD	mm	6060	6060	6270	6270	6450	7050	7870	7870	9120	9380	11650
W	STD	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/IK/EC/ECO/REC-FX 172÷302

800 | 1700 | 800 | 1700

RTA/IK/EC/ECO/REC-FX 352÷724

1000 | 1700 | 1000 | 1700



Electrical board side

NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP version are specified on technical brochure.

RTA/IK/EC/ECO/REC-WH 172÷724

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH INVERTER SCROLL COMPRESSORS, EC INVERTER PLUG-FANS, ECONOMIZER AND WHEEL HEAT RECOVERY.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Inverter Scroll compressor with R410A refrigerant and **EC Inverter Plug-Fans**. The highest efficiency at partial loads is guaranteed by the Inverter Scroll technology on compressor since its power is varied proportionally to the requested thermal load. Furthermore, the EC Inverter Plug-Fans with high energy efficiency backward blades are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity.

Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The ECO/REC-WH units have an high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, an **ECONOMIZER** automatically controlled both in FREE-COOLING or FREE-HEATING and a **WHEEL HEAT RECOVERY**, able to treat up to 100% of total air flow.



INVERTER SCROLL

EC INVERTER PLUG FANS

VERSION

RTA/IK/EC/ECO/REC-WH

Cooling only with EC Inverter Plug-Fans, Economizer and Wheel Heat Recovery

RTA/IK/EC/WP/ECO/REC-WH

Reversible Heat Pump with EC Inverter Plug-Fans, Economizer and Wheel Heat Recovery

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- DC INVERTER Scroll and ON-OFF Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section, contactors for the fan motors of the air handling section.
- Electronic proportional device to decrease the sound level, with a continuous regulation of the fan speed. This device also allows the cooling functioning of the unit by external temperature till -20°C.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control

AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
CH	Enthalpic control (ECO only)
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface

ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			172	192	212	232	272	302	352	372	484	574	724
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.53	3.53	3.72	3.89	3.77	3.55	3.74	3.94	3.62	3.81	3.55
	Energy Efficiency (3)	%	138	138	146	153	148	139	147	155	142	149	139
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.22	3.34	3.34	3.37	3.54	3.22	3.54	3.38	3.33	3.54	3.23
	Energy Efficiency (5)	%	126	131	131	132	139	126	139	132	130	139	126
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Air intake section	Filter	Typo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
Condensing section	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
	Compressor	n°	2	2	2	2	2	2	2	2	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
Hot water coil	Capacity steps	n°	Stepless										
	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
	Power supply	V/Ph/Hz	400/3/50										
Electrical heater	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
	Power supply	V/Ph/Hz	400/3/50										
Electrical characteristics	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
Sound pressure (7)		dB(A)	57	57	57	57	57	58	59	59	60	60	61
Weights	Transport weight	Kg	1645	1720	1910	2020	2040	2210	2640	2690	3260	3590	4390
	Operating weight	Kg	1620	1695	1885	1995	2015	2185	2610	2660	3225	3555	4350

ECONOMIZER AND WHEEL HEAT RECOVERY

ECO/REC-WH. Further to the components of the ECO section, includes: high efficiency wheel-type heat recovery device made of aluminium with hygroscopic treatment, managed by a constant-speed electric motor, with moisture drain pan and dampers with spring return (fresh air damper + air recirculation damper + exhaust air damper). Also the adjustment of this section is included into the unit control.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			172	192	212	232	272	302	352	372	484	574	724
L	STD	mm	6060	6060	6270	6270	6450	7050	7870	7870	9120	9380	11650
W	STD	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/IK/EC/ECO/REC-WH 172÷302



RTA/IK/EC/ECO/REC-WH 352÷724



NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP version are specified on technical brochure.

RTA/K 182÷804

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH SCROLL COMPRESSORS AND RADIAL FANS OR EC INVERTER PLUG-FANS.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Scroll compressors with R410A refrigerant and radial fans or **EC Inverter Plug-Fans**. The EC Inverter Plug-Fans with high energy efficiency backward blades both for intake as well as delivery are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version. The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.



EC INVERTER PLUG FANS

VERSION

RTA/K

Cooling only with radial fans

RTA/K/WP

Reversible Heat Pump with radial fans

RTA/K/EC

Cooling only with EC Inverter Plug-Fans

RTA/K/EC/WP

Reversible Heat Pump with EC Inverter Plug-Fans

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- Delivery radial fans coupled to 3-phase motors by V belt and variable pulley.
- High efficiency delivery reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencing
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
CT	Condensing control down to 0 °C
CC	Condensing control down to -20 °C
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control

AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			182	202	242	262	302	363	393	453	524	604	804
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.26	3.32	3.49	3.65	3.54	3.28	3.51	3.70	3.39	3.57	3.33
	Energy Efficiency (3)	%	127	130	137	143	139	128	137	145	133	140	130
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.09	3.21	3.21	3.24	3.41	3.09	3.40	3.25	3.20	3.40	3.11
	Energy Efficiency (5)	%	121	125	125	127	133	121	133	127	125	133	121
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	1	1	1	1	1	1	1	1	1
Air treatment section (EC version)	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Condensing section	Compressor	n°	2	2	2	2	2	3	3	3	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
	Capacity steps	n°	2			2			3			4	
Hot water coil	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
Electrical heater	Power supply	V/Ph/Hz	400/3/50										
	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50										
	Max. running current	A	50	53	63	67	76	94	100	109	133	150	173
	Max. starting current	A	173	175	186	199	243	218	232	276	265	317	347
Electrical characteristics (EC version)	Power supply	V/Ph/Hz	400/3/50										
	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
Sound pressure	STD version (7)	dB(A)	58	58	58	58	58	59	60	60	61	61	62
	EC version (7)	dB(A)	57	57	57	57	57	58	59	59	60	60	61
Weights	Transport weight	Kg	1030	1085	1180	1280	1300	1540	1900	1950	2270	2480	3320
	Operating weight	Kg	1015	1070	1165	1265	1285	1520	1880	1930	2250	2460	3290
Weights (EC version)	Transport weight	Kg	990	1050	1150	1250	1260	1450	1810	1860	2230	2400	3180
	Operating weight	Kg	975	1035	1135	1235	1245	1430	1790	1840	2210	2380	3150

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			182	202	242	262	302	363	393	453	524	604	804
L	STD/EC	mm	2980	3080	3190	3190	3290	3770	4500	4500	5150	5300	7370
W	STD/EC	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/EC	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/K 182÷363



RTA/K 393÷804



NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP versions are specified on technical brochure.

RTA/K/MS 182÷804

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH SCROLL COMPRESSORS, RADIAL FANS OR EC INVERTER PLUG-FANS AND MIXING BOX.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Scroll compressors with R410A refrigerant and radial fans or **EC Inverter Plug-Fans**. The EC Inverter Plug-Fans with high energy efficiency backward blades both for intake as well as delivery are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version. The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards. The MS units have an high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, a **MIXING BOX**.



EC INVERTER PLUG FANS

VERSION

RTA/K/MS

Cooling only with radial fans and Mixing Box

RTA/K/WP/MS

Reversible Heat Pump with radial fans and Mixing Box

RTA/K/EC/MS

Cooling only with EC Inverter Plug-Fans and Mixing Box

RTA/K/EC/WP/MS

Reversible Heat Pump with EC Inverter Plug-Fans and Mixing Box

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- Delivery radial fans coupled to 3-phase motors by V belt and variable pulley.
- High efficiency delivery reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
CT	Condensing control down to 0 °C
CC	Condensing control down to -20 °C
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control
AT/P	Constant available static pressure regulation control

WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			182	202	242	262	302	363	393	453	524	604	804	
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252	
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1	
Cooling (EN14511)	SEER (3)		3.26	3.32	3.49	3.65	3.54	3.28	3.51	3.70	3.39	3.57	3.33	
	Energy Efficiency (3)	%	127	130	137	143	139	128	137	145	133	140	130	
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262	
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5	
Heating (EN14511)	SCOP (5)		3.09	3.21	3.21	3.24	3.41	3.09	3.40	3.25	3.20	3.40	3.11	
	Energy Efficiency (5)	%	121	125	125	127	133	121	133	127	125	133	121	
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31	
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250	
	Fan	n°	1	1	1	1	1	1	1	1	1	1	1	
Air treatment section (EC version)	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31	
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250	
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4	
Condensing section	Filter	Tipò	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	
	Compressor	n°	2	2	2	2	2	3	3	3	4	4	4	
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2	
Hot water coil	Capacity steps	n°	2				3				4			
	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350	
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57	
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36	
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45	
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"	
	Power supply	V/Ph/Hz	400/3/50											
Electrical heater	Heating capacity	kW	15	21	27	27	27	41	41	41	48	55		
	Max. absorbed current	A	22	30	39	39	39	59	59	59	69	79		
	Steps	n°	2	2	2	2	2	4	4	4	4	4		
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50											
	Max. running current	A	50	53	63	67	76	94	100	109	133	150	173	
	Max. starting current	A	173	175	186	199	243	218	232	276	265	317	347	
Electrical characteristics (EC version)	Power supply	V/Ph/Hz	400/3/50											
	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170	
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344	
Sound pressure	STD version (7)	dB(A)	58	58	58	58	58	59	60	60	61	61	62	
	EC version (7)	dB(A)	57	57	57	57	57	58	59	59	60	60	61	
Weights	Transport weight	Kg	1110	1170	1285	1380	1400	1610	2000	2050	2370	2600	3570	
	Operating weight	Kg	1095	1155	1265	1360	1380	1590	1980	2030	2350	2580	3540	
Weights (EC version)	Transport weight	Kg	1070	1135	1245	1340	1360	1560	1940	1990	2300	2520	3465	
	Operating weight	Kg	1055	1120	1225	1320	1340	1540	1920	1970	2280	2500	3435	

MIXING BOX

MS. Further to components of the basic section, includes two wing profile aluminium dampers with spring return servomotors; the opposite movement is ensured by transmission of nylon gear.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			182	202	242	262	302	363	393	453	524	604	804
L	STD/EC	mm	3430	3530	3640	3640	3740	4220	4950	4950	5600	5750	7850
W	STD/EC	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/EC	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA



NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP versions are specified on technical brochure.

RTA/K/ECO 182÷804

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH SCROLL COMPRESSORS, RADIAL FANS OR EC INVERTER PLUG-FANS AND ECONOMIZER.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Scroll compressors with R410A refrigerant and radial fans or **EC Inverter Plug-Fans**. The EC Inverter Plug-Fans with high energy efficiency backward blades both for intake as well as delivery are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The ECO units have a high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, an **ECONOMIZER** automatically controlled both in FREE-COOLING or FREE-HEATING.

The unit can be equipped, as an option, with the innovative **Thermodynamic Coil-Boost Heat Recovery** to achieve better performance and efficiency both in cooling and heating up to 15%.



EC INVERTER PLUG FANS

THERMODYNAMIC COIL-BOOST HEAT RECOVERY

VERSION

RTA/K/ECO

Cooling only with radial fans and Economizer

RTA/K/WP/ECO

Reversible Heat Pump with radial fans and Economizer

RTA/K/EC/ECO

Cooling only with EC Inverter Plug-Fans and Economizer

RTA/K/EC/WP/ECO

Reversible Heat Pump with EC Inverter Plug-Fans and Economizer

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- Delivery & intake radial fans coupled to 3-phase motors by V belt and variable pulley.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencing
THCB	Thermodynamic Coil-Boost Heat Recovery (ECO only)
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
CT	Condensing control down to 0 °C
CC	Condensing control down to -20 °C
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins
FT/M	Soft bag filters efficiency M6-F7-F8

FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control
AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
CH	Enthalpic control (ECO only)
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface
ISB	BACnet MSTP protocol, RS485 serial interface

ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers

MODEL			182	202	242	262	302	363	393	453	524	604	804
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.26	3.32	3.49	3.65	3.54	3.28	3.51	3.70	3.39	3.57	3.33
	Energy Efficiency (3)	%	127	130	137	143	139	128	137	145	133	140	130
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.09	3.21	3.21	3.24	3.41	3.09	3.40	3.25	3.20	3.40	3.11
	Energy Efficiency (5)	%	121	125	125	127	133	121	133	127	125	133	121
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	1	1	1	1	1	1	1	1	1
	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
Air treatment section (EC version)	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
Air intake section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
	Fan	n°	1	1	1	1	1	1	1	1	1	1	1
Air intake section (EC version)	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Condensing section	Compressor	n°	2	2	2	2	3	3	3	3	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
	Capacity steps	n°			2				3			4	
Hot water coil	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1½"	1½"	1½"	1½"	1½"	2"	2"	2"	2"	2½"	2½"
Electrical heater	Power supply	V/Ph/Hz	400/3/50										
	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50										
	Max. running current	A	50	53	63	67	76	94	100	109	133	150	173
	Max. starting current	A	173	175	186	199	243	218	232	276	265	317	347
Electrical characteristics (EC version)	Power supply	V/Ph/Hz	400/3/50										
	Max. starting current	A	46	47	56	60	69	88	93	102	126	148	170
Sound pressure	STD version (7)	dB(A)	58	58	58	58	58	59	60	60	61	61	62
	EC version (7)	dB(A)	57	57	57	57	57	58	59	59	60	60	61
Weights	Transport weight	Kg	1570	1690	1810	1910	1930	2160	2560	2610	3130	3500	4520
	Operating weight	Kg	1550	1670	1790	1890	1910	2135	2535	2585	3100	3465	4480
Weights (EC version)	Transport weight	Kg	1500	1610	1740	1840	1860	2000	2400	2450	3020	3370	4190
	Operating weight	Kg	1480	1590	1720	1820	1840	1975	2375	2425	2990	3335	4150

ECONOMIZER

ECO. Further to components of the basic section, includes: return air fan with electrical motor, complete of adjustable transmission, mounted on elastic supports; motorized wing profile aluminium dampers, the opposite movement is ensured by transmission of nylon gear. Exhaust, recirculation and fresh air are controlled through the microprocessor fitted in the base unit; this microprocessor, according to the temperature of the return and fresh air, modulates the opening of the dampers and controls the cooling circuit capacity steps to ensure comfort conditions of the handled air. The adjustments of the ECO versions are automatically controlled both in free-cooling and free-heating mode.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			182	202	242	262	302	363	393	453	524	604	804
L	STD/EC	mm	5260	5480	5570	5570	5650	6170	6900	6900	8080	8470	11020
W	STD/EC	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/EC	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/K/ECO 182÷363



RTA/K/ECO 393÷804



Electrical board side

NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP versions are specified on technical brochure.

RTA/K/ECO/REC-FX 182÷804

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH SCROLL COMPRESSORS, RADIAL FANS OR EC INVERTER PLUG-FANS, ECONOMIZER AND CROSS-FLOW HEAT RECOVERY.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Scroll compressors with R410A refrigerant and radial fans or **EC Inverter Plug-Fans**. The EC Inverter Plug-Fans with high energy efficiency backward blades both for intake as well as delivery are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The ECO/REC-FX units have an high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, an **ECONOMIZER** automatically controlled both in FREE-COOLING or FREE-HEATING and a **CROSS-FLOW HEAT RECOVERY**.



EC INVERTER PLUG FANS

VERSION

RTA/K/ECO/REC-FX

Cooling only with radial fans, Economizer and Cross-flow Heat Recovery

RTA/K/WP/ECO/REC-FX

Reversible Heat Pump with radial fans, Economizer and Cross-flow Heat Recovery

RTA/K/EC/ECO/REC-FX

Cooling only with EC Inverter Plug-Fans, Economizer and Cross-flow Heat Recovery

RTA/K/EC/WP/ECO/REC-FX

Reversible Heat Pump with EC Inverter Plug-Fans, Economizer and Cross-flow Heat Recovery

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- Delivery & intake radial fans coupled to 3-phase motors by V belt and variable pulley.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers	AT/P	Constant available static pressure regulation control	ISL	LonWorks protocol, FT-10 serial interface
SL	Unit silencing	WS2	2-Row hot water coil with 3-Way valve	CP	Potential free contacts
RFM	Cooling circuit shut-off valve on discharge line	EHG	Electrical heater with step regulation	RP	Coil protection metallic guards
RFL	Cooling circuit shut-off valve on liquid line	CH	Enthalpic control (ECO only)	LOOSE ACCESSORIES	
CT	Condensing control down to 0 °C	SQ	Air quality sensor	MN	High and low pressure gauges
CC	Condensing control down to -20 °C	PF	Filter differential pressure switch	CR	Remote control panel
TXC	Condensing coil with pre-coated fins	IS	Modbus RTU protocol, RS485 serial interface	AG	Rubber shock absorbers
TXE	Evaporating coil with pre-coated fins	ISB	BACnet MSTP protocol, RS485 serial interface		
FT/M	Soft bag filters efficiency M6-F7-F8	ISBT	BACnet TCP/IP protocol, Ethernet port		
FT/R	Rigid bag filters efficiency M6-F7-F8				
AT	Constant air flow regulation control				

MODEL			182	202	242	262	302	363	393	453	524	604	804
Cooling	Cooling capacity (1)	kW	57.9	65.8	77.6	87.4	98.6	113	129	145	168	198	252
	Absorbed power (1),(2)	kW	19.4	21.8	24.6	26.2	30.8	37.8	40.4	43.3	54.6	61.5	85.1
Cooling (EN14511)	SEER (3)		3.26	3.32	3.49	3.65	3.54	3.28	3.51	3.70	3.39	3.57	3.33
	Energy Efficiency (3)	%	127	130	137	143	139	128	137	145	133	140	130
Heating	Heating capacity (4)	kW	60.2	67.2	76.8	88.6	101	115	133	151	173	204	262
	Absorbed power (2),(4)	kW	16.8	17.9	20.2	22.8	25.2	32.2	34.0	40.0	45.7	50.4	70.5
Heating (EN14511)	SCOP (5)		3.09	3.21	3.21	3.24	3.41	3.09	3.40	3.25	3.20	3.40	3.11
	Energy Efficiency (5)	%	121	125	125	127	133	121	133	127	125	133	121
Air treatment section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	1	1	1	1	1	1	1	1	1
	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
Air treatment section (EC version)	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	250	250	250	250	250	250	250	250	250	250	250
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
	Filter	Tipo	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4	G4
Air intake section	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
	Fan	n°	1	1	1	1	1	1	1	1	1	1	1
Air intake section (EC version)	Air flow	m³/s	2.67	3.30	4.05	4.05	4.84	5.49	6.32	6.32	8.20	9.79	12.31
	Available static pressure	Pa	100	100	100	100	100	100	100	100	100	100	100
	Fan	n°	1	1	2	2	2	2	2	2	2	4	4
Condensing section	Compressor	n°	2	2	2	2	2	3	3	3	4	4	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	1	2	2	2
	Capacity steps				2				3			4	
Hot water coil	Heating capacity (6)	kW	85	100	125	125	150	175	200	200	250	300	350
	Air pressure drops	Pa	30	31	31	31	31	30	36	36	35	35	57
	Water flow (6)	l/s	2.03	2.39	2.99	2.99	3.58	4.18	4.78	4.78	5.97	7.17	8.36
	Water pressure drops	kPa	45	47	48	48	49	44	51	51	53	57	45
	Water connections	"G	1"½	1"½	1"½	1"½	1"½	2"	2"	2"	2"	2 ½"	2 ½"
	Power supply	V/Ph/Hz	400/3/50										
Electrical heater	Heating capacity	kW	15	21	27	27	27	41	41	41	41	48	55
	Max. absorbed current	A	22	30	39	39	39	59	59	59	59	69	79
	Steps	n°	2	2	2	2	2	4	4	4	4	4	4
	Power supply	V/Ph/Hz	400/3/50										
Electrical characteristics	Max. running current	A	50	53	63	67	76	94	100	109	133	150	173
	Max. starting current	A	173	175	186	199	243	218	232	276	265	317	347
	Power supply	V/Ph/Hz	400/3/50										
Electrical characteristics (EC version)	Max. running current	A	46	47	56	60	69	88	93	102	126	148	170
	Max. starting current	A	169	169	179	192	236	212	225	269	258	315	344
	Power supply	V/Ph/Hz	400/3/50										
Sound pressure	STD version (7)	dB(A)	58	58	58	58	58	59	60	60	61	61	62
	EC version (7)	dB(A)	57	57	57	57	57	58	59	59	60	60	61
Weights	Transport weight	Kg	1715	1800	1980	2090	2110	2370	2800	2850	3370	3720	4720
	Operating weight	Kg	1690	1775	1955	2065	2085	2345	2770	2820	3335	3685	4680
Weights (EC version)	Transport weight	Kg	1645	1720	1910	2020	2040	2210	2640	2690	3260	3590	4390
	Operating weight	Kg	1620	1695	1885	1995	2015	2185	2610	2660	3225	3555	4350

ECONOMIZER AND CROSS-FLOW HEAT RECOVERY

ECO/REC-FX. Further to the components of the ECO section, it includes: static recovery device made of aluminium with moisture drain pan, flat filters inspectable through hinged door and dampers with return spring servomotors (fresh air damper + air recirculation damper + exhaust air damper + 2 Free-Cooling dampers). Also the adjustment of this section is included into the unit control.

COMPLEMENTARY SECTIONS

- UM Section with preparation for Humidifier
- UM/EN Section Humidifier with electrodes immersed
- F/CD Condensation endothermic hot air generator with modulating gas burner

DIMENSIONS			182	202	242	262	302	363	393	453	524	604	804
L	STD/EC	mm	6060	6060	6270	6270	6450	7050	7870	7870	9120	9380	11650
W	STD/EC	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/EC	mm	2100	2340	2340	2340	2340	2340	2340	2340	2340	2510	2510

CLEARANCE AREA

RTA/K/ECO/REC-FX 182÷363
800 | 1700 | 800 | 1700

RTA/K/ECO/REC-FX 393÷804
1000 | 1700 | 1000 | 1700



Electrical board side

NOTES

- Evaporator inlet air temperature 27 °C d.b./19 °C w.b.; ambient air temperature 35 °C.
 - Excluded the power absorbed by fans of air treatment section.
 - Seasonal energy efficiency of cooling. According to EU Regulation n. 2016/2281.
 - Condenser inlet air temperature 20 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating with average climatic conditions. According to EU Regulation n. 2016/2281.
 - Inlet air temperature 20 °C, water temperature 70/60 °C.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WP versions are specified on technical brochure.

RTA/K/ECO/REC-WH 182÷804

DOUBLE SKIN PACKAGED ROOF TOP UNITS WITH SCROLL COMPRESSORS, RADIAL FANS OR EC INVERTER PLUG-FANS, ECONOMIZER AND WHEEL HEAT RECOVERY.



The double skin packaged Roof Top units of the **AIRMAXI** series are the ideal solution for air conditioning of wide surfaces such as shopping malls and restaurants, canteens or for industrial areas. Those units feature Scroll compressors with R410A refrigerant and radial fans or **EC Inverter Plug-Fans**. The EC Inverter Plug-Fans with high energy efficiency backward blades both for intake as well as delivery are managed by an electronic control adjusting fans' rotational speed to adapt the air flow to the system capacity. Equipped with extruded aluminium alloy sections and 50mm-thick sandwich panelling, these units are available in Cooling only and Reversible Heat Pump version.

The flat or pocket filters help to keep the air quality at a suitable level in order to guarantee appropriate hygiene standards.

The ECO/REC-WH units have an high level of modularity and adaptability to every plant-engineering need: these units feature, in addition to the basic sections, an **ECONOMIZER** automatically controlled both in FREE-COOLING or FREE-HEATING and a **WHEEL HEAT RECOVERY**, able to treat up to 100% of total air flow.



EC INVERTER PLUG FANS

VERSION

RTA/K/ECO/REC-WH

Cooling only with radial fans, Economizer and Wheel Heat Recovery

RTA/K/WP/ECO/REC-WH

Reversible Heat Pump with radial fans, Economizer and Wheel Heat Recovery

RTA/K/EC/ECO/REC-WH

Cooling only with EC Inverter Plug-Fans, Economizer and Wheel Heat Recovery

RTA/K/EC/WP/ECO/REC-WH

Reversible Heat Pump with EC Inverter Plug-Fans, Economizer and Wheel Heat Recovery

FEATURES

- Structure of base perimeter made of steel sheet elements galvanised. Frame made of extruded aluminium alloy profiles connected by 3 way joints. Assembling of the base to the frame is of dual support and grants the walking on the base panels installation without sticking out screws. 50mm thick sandwich panels made of prepainted steel sheet; water proofing granted by gaskets having shape memory for perfect seal up even after repeated removals. Section connection is effected by means of assembling conic stirrups and water proofing is granted by gaskets.
- Scroll compressors with oil sight glass, internal overheat protection and crankcase heater.
- Condenser and evaporator with copper tube and aluminium finned coil.
- Delivery & intake radial fans coupled to 3-phase motors by V belt and variable pulley.
- High efficiency delivery & intake reverse blade EC INVERTER PLUG-FANS, with electronic speed control to easily adapt to the system characteristics.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: door interlocking isolator, fuses, thermal protection relays on compressors, thermocontacts for the fans of the condensing section and contactors for the fan motors of the air handling section.
- Microprocessor for the automatic control of the unit.

ACCESSORIES

FACTORY FITTED ACCESSORIES

IM	Automatic circuit breakers
SL	Unit silencement
RFM	Cooling circuit shut-off valve on discharge line
RFL	Cooling circuit shut-off valve on liquid line
CT	Condensing control down to 0 °C
CC	Condensing control down to -20 °C
TXC	Condensing coil with pre-coated fins
TXE	Evaporating coil with pre-coated fins

FT/M	Soft bag filters efficiency M6-F7-F8
FT/R	Rigid bag filters efficiency M6-F7-F8
AT	Constant air flow regulation control
AT/P	Constant available static pressure regulation control
WS2	2-Row hot water coil with 3-Way valve
EHG	Electrical heater with step regulation
CH	Enthalpic control (ECO only)
SQ	Air quality sensor
PF	Filter differential pressure switch
IS	Modbus RTU protocol, RS485 serial interface

ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
CP	Potential free contacts
RP	Coil protection metallic guards

LOOSE ACCESSORIES

MN	High and low pressure gauges
CR	Remote control panel
AG	Rubber shock absorbers